

CLAIMS

What Is Claimed Is:

1. A method for synchronizing circuit related objects
5 between a network management system (NMS) and a network
control processor (NCP), the method comprising:
translating data for the circuit related objects from
binary data to ASCII data in the network control
processor;
10 receiving into the network management system server the
ASCII data from the network control processor;
parsing the ASCII data; and
storing the ASCII data in a network management system
database.
15
2. The method of Claim 1, wherein the data for the circuit
related objects is stored in a persistence table in the
network control processor.
- 20 3. The method of Claim 2, wherein the step of translating
data comprises receiving an "rsh" UNIX command to
translate the persistence table from a binary
persistence table to an ASCII persistence table.

4. The method of Claim 3, wherein the step of receiving the ASCII data comprises receiving an "rcp" UNIX command to copy the ASCII persistence table to a network management system database.
- 5
5. The method of Claim 1, wherein an accessible directory in a host machine has a remote machine's host name and a user name, wherein the network management system is the remote machine, and wherein the network control processor
- 10 is the host machine.
6. The method of Claim 2, wherein the format of an ASCII persistence table is a plain text file which maintains all available records for a type of circuit related
- 15 object in the network control processor, and wherein each record includes a unique key and group of names with corresponding values, and each unique key is used to identify an individual circuit.
- 20 7. The method of Claim 6, wherein the step of parsing comprises:
reading all records from the ASCII persistence table;
and parsing the records to an network management system desired format.
- 25

8. The method of Claim 1, further comprising comparing the ASCII data with a corresponding circuit related object table already in the network management system database.

5 9. The method of Claim 8, further comprising:
detecting a mismatch between the ASCII data and the
corresponding circuit related object table; and
updating the network management system database
accordingly.

10

10. A computer-readable medium carrying one or more sequences
of one or more instructions for synchronizing circuit
related objects between a network management system (NMS)
and a network control processor (NCP), the one or more
15 sequences of one or more instructions including
instructions which, when executed by one or more
processors, cause the one or more processors to perform
the steps of:

translating data for the circuit related objects from
20 binary data to ASCII data in the network control
processor;
receiving into the network management system server the
ASCII data from the network control processor;
parsing the ASCII data; and

storing the ASCII data in a network management system
database.

11. The computer-readable medium of Claim 10, wherein the
5 data for the circuit related objects is stored in a
persistence table in the network control processor.
12. The computer-readable medium of Claim 11, wherein the
step of translating data comprises the processor
10 receiving an "rsh" UNIX command to translate the
persistence table from a binary persistence table to an
ASCII persistence table.
13. The computer-readable medium of Claim 12, wherein the
15 step of receiving the ASCII data comprises the processor
receiving an "rcp" UNIX command to copy, the ASCII
persistence table to a network management system
database.
- 20 14. The computer-readable medium of Claim 10, wherein an
accessible directory in a host machine has a remote
machine's host name and a user name, wherein the network
management system is the remote machine, and wherein the
network control processor is the host machine.

25

15. The computer-readable medium of Claim 11, wherein the format of an ASCII persistence table is a plain text file which maintains all available records for a type of circuit related object in the network control processor, and wherein each record includes a unique key and group of names with corresponding values, and each unique key is used to identify an individual circuit.
16. The computer-readable medium of Claim 15, wherein the step of parsing causes the processor to perform the steps of:
reading all records from the ASCII persistence table; and
parsing the records to an network management system
desired format.
17. The computer-readable medium of Claim 10, wherein the instructions further cause the processor to perform the step of comparing the ASCII data with a corresponding circuit related object table already in the network management system database.
18. The computer-readable medium of Claim 17, wherein the instructions further cause the processor to perform the steps of:

detecting a mismatch between the ASCII data and the
corresponding circuit related object table; and
updating the network management system database
accordingly.

5

2006-04-28 14:00:00